



Material/Finish



|                | SRFXS                |
|----------------|----------------------|
| Main Body      | Equivalent to SUS304 |
| Strength Class | Equivalent to A2-50  |

- Flat head bolt with a pin at the center of the hexalobular socket \*1.
- This prevents mounting and removing with regular tools.
- Install and remove with **SRX** Dedicated Wrench or **SRXB** Dedicated Bit and **SRD** Dedicated Magnetic Screwdriver together.

\* 1 : The hexalobular shape is prescribed by JIS B 1015: 2008(ISO 10664: 2005)"Hexalobular internal driving feature for bolts and screws".

Application

Equipment/devices disassembly/tampering prevention  
Theft prevention for outdoor facilities  
Security measures  
Safety measures



| Part Number | M (Coarse)        |       | L |   |    |    |    |    |    |    | D1 | L1   | Applicable Wrench Type | Applicable Bit Type |          | Hexalobular Socket No. | Mass (g)    | Qty per Pack |
|-------------|-------------------|-------|---|---|----|----|----|----|----|----|----|------|------------------------|---------------------|----------|------------------------|-------------|--------------|
|             | Nominal of Thread | Pitch |   |   |    |    |    |    |    |    |    |      |                        | Bit                 | Driver   |                        |             |              |
| SRFXS-M3    | M3                | 0.5   | 6 | 8 | 10 | 12 |    |    |    |    | 6  | 1.75 | SRX-10                 | SRXB-10             | SRD-6.35 | 10                     | 0.48 - 0.72 | 10           |
| SRFXS-M4    | M4                | 0.7   |   | 8 | 10 | 12 | 16 | 20 |    |    | 8  | 2.3  | SRX-20                 | SRXB-20             | SRD-6.35 | 20                     | 1 - 1.9     | 10           |
| SRFXS-M5    | M5                | 0.8   |   | 8 | 10 | 12 | 16 | 20 | 25 |    | 10 | 2.8  | SRX-25                 | SRXB-25             | SRD-6.35 | 25                     | 1.9 - 3.9   | 10           |
| SRFXS-M6    | M6                | 1     |   |   | 10 | 12 | 16 | 20 | 25 | 30 | 12 | 3.4  | SRX-30                 | SRXB-30             | SRD-6.35 | 30                     | 3.3 - 7     | 10           |

When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

Related Products

Washer for Flat Head Screw  
**SWAS-RW** is available.



**SRX** dedicated wrenches are available.



**SRXB** applicable bits are available.



Dedicated magnetic screwdrivers **SRD** are available.



Part Number Specification

SRFXS-M5-16

1

2

|                          |                            |                          |                          |                                      |
|--------------------------|----------------------------|--------------------------|--------------------------|--------------------------------------|
| Individual Sales         | Cleanroom Wash & Packaging | Screw Length Adjustment  | Vibration Resistant      | Modification process for captive use |
| Available / Add'l charge | Available / Add'l charge   | Available / Add'l charge | Available / Add'l charge | Not Available                        |