




SRBS Hexalobular Socket (with Pin) Button Head Cap Screws

Tamper Resistance **SUS** Stainless steel



Material/Finish



	SRBS
Main Body	Equivalent to SUS304
Strength Class	Equivalent to A2-50



- Button head cap screws with a pin at the center of the hexalobular socket*1.
- This prevents mounting and removing with regular tools.
- Install and remove with **SRX** Dedicated Wrench or **SRXB** Dedicated Bit and **SRD** Dedicated Magnetic Screwdriver together.

*1: The hexalobular shape is prescribed by JIS B 1015: 2008(ISO 10664: 2005)"Hexalobular internal driving feature for bolts and screws".

Application

Equipment/devices disassembly/tampering prevention
Theft prevention for outdoor facilities
Security measures
Safety measures

Unit : mm																						
Part Number	M (Coarse)		L												D1	L1	Applicable Wrench Type	Applicable Bit Type		Hexalobular Socket No.	Mass (g)	Qty per Pack
	Nominal of Thread	Pitch																Bit	Driver			
SRBS-M3	M3	0.5	6	8	10	12	15	16	20	25	30	35	40	5.7	1.65	SRX-10	SRXB-10	SRD-6.35	10	0.48 - 1.4	20	
SRBS-M4	M4	0.7	6	8	10	12	15	16	20	25	30	35	40	7.6	2.2	SRX-20	SRXB-20	SRD-6.35	20	1.1 - 4.2	20*1	
SRBS-M5	M5	0.8	8	10	12	15	16	20	25	30	40			9.5	2.75	SRX-25	SRXB-25	SRD-6.35	25	1.8 - 6.4	20	
SRBS-M6	M6	1	8	10	12	15	16	20	25	30	40	50		10.5	3.3	SRX-30	SRXB-30	SRD-6.35	30	3 - 12	10	
SRBS-M8	M8	1.25		10	12		16	20	25	30	40	50	14	4.4	SRX-40	SRXB-40	SRD-6.35	40	7.3 - 22	10		

Unit : mm

*1: Quantity per pack for **SRBS-M4-35** and **SRBS-M4-40** is 1.

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

Related Products

SRX dedicated wrenches are available.



SRXB applicable bits are available.



Dedicated magnetic screwdrivers **SRD** are available.



Part Number Specification

SRBS-M5-16

1

2

1 Individual Sales	1 Cleanroom Wash & Packaging	1 Screw Length Adjustment	1 Vibration Resistant	1 Modification process for captive use
Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Available / Add'l charge